

Administration
(513) 722-3400

Planning / Zoning
(513) 722-3400

Service / Cemetery
(513) 722-3400



Police
(513) 722-3200

Fire / E.M.S.
(513) 722-3500

www.goshen-oh.gov
6757 Goshen Road
Goshen, Ohio 45122

IN ORDER TO BE ELIGIBLE FOR A PERMIT TO OPEN A GOSHEN TOWNSHIP STREET, APPLICANT MUST PROVIDE A \$2,000 RESTERATION BOND IN THE NAME OF GOSHEN TOWNSHIP TRUSTEES FOR EACH CUT TO BE MADE, INDENTIFIED BY EXACT LOCATION.

THIS BOND MUST BE PRESENTED BEFORE A PERMIT IS ISSUED AND MUST REMAIN IN EFFECT UNTIL IT IS RELEASED BY GOSHEN TOWNSHIP IN WRITING, AT LEAST ONE YEAR FROM DATE OF RESTORATION.

BOND HAS BEEN POSTED WITH GOSHEN TOWNSHIP TRUSTEES IN THE AMOUNT OF \$_____

BONDING COMPANY_____ BOND #_____

ISSUE DATE_____

THE RECIPENT OF THIS PERMIT _____
EXPRESSLY AGREES TO DO ALL WORK OF EXCAVATION, REFILLING AND TEMPORY AND/OR PERMANENT
REPAIRINGIN ACCORDANCE WITH THE RULES AND REGUALTIONS OF GOSHEN TOWNSHIP, OHIO WHICH ARE
ATTACED TO THIS PERMIT.

SERVICE OF CONTRACTOR/AGENT DATE

STREET OPENING PERMIT

PERMIT NUMBER_____ DATE_____

PERMISION IS HERBY GRANTED TO:

ADDRESS_____

CONTRACT PERSON_____

COMPANY PHONE NUMBER: BUISNESS HOURS_____ AFTER NORMAL HOURS_____
TO: BORE_____ OPEN CUT_____

STREET_____ BETWEEN_____ AND_____

FOR THE PURPOSE OF:_____

SIZE AND TYPE OF OPENING: SOD_____ ASPHALT_____ CONCRETE_____

PERMIT ISSUED BY:_____ TITLE:_____

AGENT, GOSHEN TOWNSHIP

\$50 FEE COLLECTED_____ RECEIPT #_____ DATE OF FINAL RESOTRATION_____

FOR ANY QUESTIONS OR TO SET UP AN INSPECTION TIME CONTACT **CHAD MEADOWS** @ CELL 513-616-4074
OR OFFICE 513-722-3400 EXT 323. ANY EMERGENCY PLEASE CALL 911 TO LOCATE UTILITIES PLEASE CALL
OHIO811,8-1-1 OR (800)362-2764

Administration
(513) 722-3400

Planning / Zoning
(513) 722-3400

Service / Cemetery
(513) 722-3400



Police
(513) 722-3200

Fire / E.M.S.
(513) 722-3500

www.goshen-oh.gov
6757 Goshen Road
Goshen, Ohio 45122

RULES AND REGULATIONS

FOR ALL OPEN CUTS IN GOSHEN TOWNSHIP

- A. Open cuts (asphalt and concrete in roadways)
 1. All streets are to be bored or tunneled unless otherwise approved by the issuing agent or inspector.
 2. Open cutting in roadway
 - a. All cuts in roadway will be saw-cut
 - b. If left open after working hours, a 2" plate minimum will be placed over cut and pinned at all corners.
 - c. Road work will be done between 9 a.m. and 3 p.m. or after 6 p.m. until 6 a.m. unless otherwise approved by issuing agent
 - d. The contractor will be responsible for all traffic control signs and devices for the continued flow of traffic.
 - e. Contractor will use flaggers when working on two-lane roads when one lane is to be closed to traffic.
 3. Backfill for all roadway open cuts will be lass fill.
 4. Flash fill will come within 10" of final grade.
 5. If cut is to be replaced with asphalt, it will be done in two 5" lifts.
 - a. The first lift will be 301 base course
 - b. Final course will be done with 404.
 - c. Both lifts will be compacted when being put in place.
 - d. Final course to be trimmed, and all vertical joins to be sealed. (see attached detail A)

**6757 Goshen Road
Goshen, Ohio 45122**

Administration
(513) 722-3400

Planning / Zoning
(513) 722-3400

Service / Cemetery
(513) 722-3400



Police
(513) 722-3200

Fire / E.M.S.
(513) 722-3500

www.goshen-oh.gov
6757 Goshen Road
Goshen, Ohio 45122

6. If pavement is concrete, replace with not less than 10" of class "C" concrete and a minimum overlap of 6" (see attached detail b)
- B. Sod cuts in right of ways
1. Sod cuts will be backfilled with compactible material.
 2. Backfilling will be done in 6" lifts and compacted.
 3. 8"-12" of top soil will be put in place, seeded and strawed.
- C. Street Trees
1. Extreme care is to be taken in the area of street trees.
 2. All roots (4" and larger) are to be tunneled or bored under, not cut.
 3. Any limbs damaged due to construction are to be pruned and trimmed up.
- D. Driveway and sidewalk restoration
1. Driveway approach within street right-of-way is to be a minimum of 7" thick.
 2. Sidewalks that pass through driveway approach will be a minimum of 7" thick.
 3. Sidewalks not passing through driveways are to be minimum of 5" thick.
 4. Class "C" concrete to be used for driveways and sidewalks (see attached detail C).
- E. Jobsite Maintenance
1. All contractors shall at all times maintain the jobsite and working areas in an orderly condition.
 2. All materials are to be piled or stacked as neatly as possible.
 3. Equipment is to be parked in an orderly fashion "out of the way". Additionally, the Township shall be notified as to the location and quantity.
 4. Failure to maintain the above items shall give the Township the right to employ others to do so at the contractors expense.
- F. Night Numbers

**6757 Goshen Road
Goshen, Ohio 45122**

Administration
(513) 722-3400

Planning / Zoning
(513) 722-3400

Service / Cemetery
(513) 722-3400



Police
(513) 722-3200

Fire / E.M.S.
(513) 722-3500

www.goshen-oh.gov
6757 Goshen Road
Goshen, Ohio 45122

1. Contractors shall supply the Township with a list of at least 2 numbers for night Notification in case of emergency.
- G. Contractor is responsible for final restoration.
- H. Permanent restoration must be made within 30 days after the street is opened, unless Approved by the issuing agent.
- I. The Contruction inspector from Goshen township must be notified at least one day in advance of backfilling and final restoration.
- J. All works must be done in accordance with the Rules and Regulation set by Goshen Township and the Ohio Department of Transportaion.
- K. Failure to comply with these rules and regulations will result in the forfeiture of bond and refusal of future street opening permits.